

AIR CIRCULATORS

COMMERCIAL AIR CIRCULATORS



WALL MOUNT



PEDESTAL MOUNT

MOTOR: 1/4 HP and 1/3 HP, 3 Speed, 120V, 1 Phase, ball-bearing, open ventilated, permanently lubricated, permanent split capacitor
SWITCH: Pull Chain
CORD: 9' long SJT type 3 conductor
GUARD: Coated steel with retaining clips
POLE: Adjusts center of fan from 43" to 60"



DNow Part #	TPI Model #	Motor HP	CFM		Amps
			Low	High	
1110388	CACU 30-W	1/4	4,000	6,000	2.4
927261	CACU 30-P	1/4	5,000	6,000	2.4
1110389	CACU 30-P-HD	1/3	5,200	6,600	3.6

INDUSTRIAL AIR CIRCULATORS

MOTOR: 1/4 HP and 1/3 HP, 3 Speed, 120V, 1 Phase, ball-bearing, open ventilated, permanently lubricated, permanent split capacitor
SWITCH: Pull Chain
CORD: 9' long SJT type 3 conductor
GUARD: Coated steel with retaining clips
POLE: Adjusts center of fan from 43" to 60"



ACH 30



IHP 30-H

DNow Part #	TPI Model #	Motor HP	CFM		Amps
			Low	High	
1110381	ACH 30	1/4	4,300	5,400	2.7
1110383	IHP 30-H	1/4	4,800	6,000	3



PEDESTAL MOUNT



WALL MOUNT

MOUNTING OPTIONS

DNow Part #	TPI Model #	Type	Weight (lbs)
1110384	ACM-P	Pedestal	34
1110385	ACM-W	Wall	3

PORTABLE BLOWERS

INDUSTRIAL BELT DRIVE PORTABLE BLOWERS

- MOTOR:** Single phase, ball-bearing, permanently lubricated, capacitor start
BLADE: Steel hub, spider, & aluminum paddles (48" steel)
SWITCH: Rocker
CORD: 12' long SJT type 3 conductor
GUARD: Spiral steel wire coated (front & rear)
WHEELS: 10" rubber, 1" thick
HOUSING: Corrosion & dent resistant high density polyethylene black housing



DNOW Part #	TPI Model #	Motor HP	CFM	Amps	Volts
1110390	PB 36-B	1/2	9,000	8	120
1110392	PB 48-B	1	15,000	15	120



COMMERCIAL BELT DRIVE PORTABLE BLOWERS

- MOTOR:** 2 speed, 120V, 3.6 amp, ball-bearing, ventilated, permanently lubricated
BLADE: Aluminum
SWITCH: Rocker
CORD: 8' long SJT type 3 conductor
GUARD: Spiral Wire (front & rear)
WHEELS: 8" rubber
HOUSING: 20 gauge steel powder coated



DNOW Part #	TPI Model #	Motor HP	CFM		Amps
			Low	High	
1110980	CPB 36-B	1/3	5,000	6,200	4.8
1110981	CPB 42-B	1/2	7,000	8,700	6.5

WORKSTATION FANS

INDUSTRIAL WORKSTATION FLOOR FANS

- MOTOR:** 3-Speed, 1/8 HP, 120V, single phase, sleeve-bearing, totally enclosed (TEAO), permanently lubricated, PSC type
BLADE: Steel hub, spider, with aluminum paddles
SWITCH: Rotary
CORD: 10' long SJT type 3 conductor
GUARD: Spiral steel wire coated (front & rear)



DNOW Part #	TPI Model #	Motor HP	CFM		Amps
			Low	High	
1110394	F-18-TE	1/8	2,000	2,500	1.5