

MONKEY PUMPS"

LESS WORK & MORE MONKEY

PUMPS SO WILD, THEY HOWL!

Enter the electrifying new products from Monkey Pumps: Black Howler and Red Howler.

Get 'em! Love 'em! Pump 'em!



BLACK HOWLER

Model E-01 12 GPD @ 250 PSI



RED HOWLER

Model E-02 33 GPD @ 150 PSI

Features

- Manual Control by on-line adjustable stroke rate and stroke length
- Agency Approved for demanding outdoor and indoor applications
- · Highly Reliable timing circuit
- Circuit Protection against voltage and current upsets
- Solenoid Protection by thermal overload with auto-reset
- Water Resistant, excellent for outdoor and indoor applications
- Internally Dampened to Reduce Noise, very acceptable for household installations
- Guided Ball Check Valve Systems, to reduce back flow and enhance outstanding priming characteristics
- Premium Standard Wetted Component Materials
- Few Moving Parts and Wall Mountable
- Safe & Easy Priming with durable leak-free bleed valve assembly

Operating Benefits

Controls

Reliable metering performance

Manual Stroke Rate

10:1 Ratio

Rated "hot" for continuous duty

Manual Stroke Length

10:1 Ratio

High viscosity capacity

• Total Turndown Ratio

100:1 Ratio

• Leak-free, sealless, liquid end.


Dimensions

Model	Α	В	С	D	Е	Shipping Weight
Black Howler	5.0"	9.6"	9.5"	6.5"	8.2"	10 lbs
Red Howler	5.0"	9.9"	9.5"	6.5"	8.5"	10 lbs

NOTE: inches $\times 2.54 = cm$

Spec	Units	Black Howler	Red Howler
	GPD	12	33
Flow Rate	GPH	0.5	1.375
	LPH	1.9	5.2
Pressure Rating	PSI	250	150
	Bar	17	10
Stroke Rate	SPM	250	250
Max Viscosity	cps	1000	1000
Fluid Connection	Size	Tubing: .25" I.D.X38 O.D.	.25" FNPT
Fluid End Materials	Head & Valves	PVDF	316SS
	Seats & O-rings	TFE	TFE
	Check Balls	Ceramic	Ceramic







PEOPLE ASSUME





LESS WORK & MORE MONKEY