

MONKEY PUMPS™

MODEL
15



SPIDER MONKEY



LESS WORK - MORE MONKEY

WWW.MONKEYPUMPS.COM

MODEL
15

SPIDER MONKEY

FEATURES & BENEFITS

One Motor; Five Plunger Sizes;
316 SS - Standard Construction;
Adjustable Packing;
Pneumatic / Gas Powered;
No Lubrication Necessary;
No Springs or Diaphragms in Motor

STATS

Strokes / Minute	4 - 105
Supply Range	20 - 150 psig
Stroke Length	1" or 1/2"
Weight	8 lbs.
Height	12 in.

WWW.MONKEYPUMPS.COM

PERFORMANCE BY PLUNGER

Plunger Diameter		1/8"	3/16"	1/4"	3/8"	1/2"
Injection Rate (us gal/day)	low	0.28	0.68	1.36	2.96	4.80
	high	8.16	17.45	33.12	78.96	135.12
Amplification Ratio		140	62	35	15	8
Max Allowable Discharge Pressure		2,000	2,000	2,000	2,000	1,312



MONKEY PUMPS™

ph (504) 394-7900 fx (504) 394-7373 spider@monkeypumps.com

MODEL
25

CHIMP



FEATURES & BENEFITS

**One Motor; Five Plunger Sizes;
316 SS - Standard Construction;
Adjustable Packing;
Pneumatic / Gas Powered;
No Lubrication Necessary;
No Springs or Diaphragms in Motor**

STATS

Strokes / Minute	1 - 105
Supply Range	20 - 150 psig
Stroke Length	1" or 1/2"
Weight	11 lbs.
Height	12 in.

WWW.MONKEYPUMPS.COM

PERFORMANCE BY PLUNGER

Plunger Diameter	1/8"	3/16"	1/4"	3/8"	1/2"
Injection Rate	0.07	0.17	0.34	0.74	1.20
(us gal/day)	8.16	17.45	33.12	78.96	135.12
low					
high					
Amplification Ratio	399	176	99	43	24
Max Allowable Discharge Pressure	12,000	12,000	12,000	6,450	3,600



MONKEY PUMPS™

ph (504) 394-7900 fx (504) 394-7373 chimp@monkeypumps.com

MONKEY PUMPS™

MODEL
50



ORANGUTAN



WWW.MONKEYPUMPS.COM



ORANGUTAN



FEATURES & BENEFITS

One Motor; Three Plunger Sizes;
316 SS - Standard Construction;
Adjustable Packing;
Pneumatic / Gas Powered;
No Lubrication Necessary;
No Springs or Diaphragms in Motor

STATS

Stroke / Minute	1-85
Supply Range	20-150 psig
Piston Diameter	5.00 in
Stroke Length	1" or 1/2"
Weight	20 lbs.
Height	13.25 in.

PERFORMANCE BY PLUNGER

Plunger Diameter		1/2"	3/4"	1"
Injection Rate (us gal/day)	low	1.50	3.00	5.00
	high	81.00	230.00	375.00
Power Amplification Ratio		99	43	24
Max Allowable Discharge Pressure		10,000	6,450	3,600



MONKEY PUMPS™

ph (504) 394-7900 fx (504) 394-7373 orangutan@monkeypumps.com



ORANGUTAN



FEATURES AND BENEFITS

One Motor; Three Plunger Sizes;
316 SS - Standard Construction;
Adjustable Packing;
Pneumatic / Gas Powered;
No Lubrication Necessary;
No Springs or Diagrams in Motor

STATS

Stroke /Minute	1-85
Supply Range	1.4 - 10.3 BAR
Piston Diameter	12.7 cm
Stroke Length	2.5 or 1.3 cm
Weight	9 kg
Height	34 cm

PERFORMANCE BY PLUNGER

Plunger Diameter (cm)	1.3	1.9	2.5
Injection Rate	6	16	19
(liter/day)	307	871	1,344
Power Amplification Ratio	99	43	24
Max Allowable Discharge Pressure	689	445	248



MONKEY PUMPS™

ph (504) 394-7900

fx (504) 394-7373

orangutan@monkeypumps.com